

## WANT A COMPACT, HIGHLY EFFICIENT MULTIFUNCTIONAL DEVICE?

With KYOCERA's unique ECOSYS technology, this multifunctional device has been designed for long life and advanced reliability whilst reducing environmental impact and cutting printing costs. It is perfect for workgroups that require a high level of functionality, easily accessible by touch panel. It represents the smart choice for eco-friendly, cost-conscious offices.

- Up to 30/15 pages A4/A3 per minute
- Time to first copy: 7.8 seconds or less
- Professional print, copy, colour scan and optional fax functionality
- Paper capacity up to 1,600 sheets and a range of paper-handling options
- Easy to install and operate
- Easy to use colour touch panel with wizard-style navigation
- Low noise emissions, 0.9W low power in sleep-mode
- Compact, 360° all-round stylish design suitable for any office
- Long-life components provide unprecedented efficiency and reliability
- HyPAS™ solution platform enables powerful customisation



Customisable, colour touch panel offers fast, easy access to frequently used functions.

By using long life components, toner is the only consumable that needs to be replaced during 300,000 pages.



# FS-6530MFP

A3 MONOCHROME MULTIFUNCTIONAL

**ECOSYS** stands for ECOlogy, ECONomy and SYSTEM-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership of maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

## PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

## KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and provides ideal network administration. It also supports the standardised SNMP protocol.

## Command Center RX

The Command Center RX enables the control and management of various settings by accessing the device via Web browser. E.g. automatic updating of screens, customising user screens, viewing department & restriction settings.

## HyPAS™ – Hybrid Platform for Advanced Solutions

KYOCERA's powerful software development platform enables users to customise the functionality and operations of the multifunctional device to their individual requirements.

## General

**Technology:** KYOCERA ECOSYS, Mono Laser, HyPAS™ solution platform

**Engine speed:** Up to 30/15 pages A4/A3 per minute

**Resolution:** 600 x 600 dpi (print), 600 x 600 dpi (scan/copy)

**Warm-up time:** Approx. 20 seconds or less

**Time to first print:** Approx. 8 seconds or less

**Time to first copy:** Approx. 9.2 seconds or less (DP), 7.8 seconds or less (Platen Cover)

**CPU:** PowerPC 464 / 800 MHz

**Memory:** Standard 1GB, max. 2GB

**Standard interface:** USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10/100/1000Base-TX, slot for optional print server, slot for optional CompactFlash®-Card

**Integrated accounting:** 100 department codes

**Dimensions with document processor (WxDxH):** 760 x 760 x 911 mm

**Weight with document processor:** Approx. 70kg including toner container

**Power source:** AC 220 ~ 240 V, 50/60 Hz

### Power consumption

Printing: 560 W

Ready-mode: 114 W

Sleep-mode: 0.9 W

**Noise (sound pressure level: ISO 7779/ISO 9296)**

Copying/Printing: 47.1 dB(A)

Stand-by: 27.1 dB(A)

**Safety standards:** TÜV/GS, CE

This unit is manufactured according to the ISO 9001 quality standard and ISO 14001 environmental standards.

## Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA and use under normal environmental conditions.

**Input capacity:** 100-sheet multi-purpose tray, 45–256 g/m<sup>2</sup> (52–163 g/m<sup>2</sup> for larger than A4/Letter size), A3, A4, A5, A6, B5, Letter, Legal, Folio, Envelopes, Custom (98 x 148 to 297 x 432 mm)  
500-sheet universal paper cassette, 60–163 g/m<sup>2</sup>, A3, A4, A5, B5, Letter, Legal, Folio, max. input capacity with options: 1,600 sheets

**Duplex unit:** Duplex as standard supports 60–163 g/m<sup>2</sup>

**Reversing document processor:** 50-sheet, Simplex scan 45–160 g/m<sup>2</sup>, Duplex scan 50–120 g/m<sup>2</sup>, A3, A4, A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm)

**Output capacity:** Max. 300 sheets; 250 sheets face-down (Main Tray) plus 50 sheets (Job Separator Tray)

## Print functions

**Controller language:** PRESCRIBE IIe

**Emulations:** PCL 6 (5e/XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

**Operating systems:** All current Windows operating systems, MAC OS X Version 10.4 or higher, Unix, Linux as well as other operating systems on request

**Fonts/barcodes:** 93 outline fonts (PCL 6, KPDL3) + 8 (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

**Features:** encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, Private Print

## Copy functions

**Max. original size:** A3/Ledger

**Continuous copying:** 1–999

**Zoom range:** 25–400% in 1% steps

**Pre-set magnification ratios:** 5 Reductions / 5 Enlargements

**Exposure mode:** Auto, manual: 7 steps

**Image adjustments:** Text, Photo, Text + Photo, Graphic/Map, Copy/Printout

**Features:** Scan-once-copy-many, electronic sort, 2in1, 4in1, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through

## Scan functions

**Functionality:** Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA, WSD scan

**Scan speed:** 40 ipm (300dpi, A4, b/w), 20 ipm (300dpi, A4, colour)

**Scan resolution:** 600, 400, 300, 200 dpi (256 greyscales per colour)

**Max. scan size:** A3, Ledger

**Original recognition:** Text, photo, text + photo, optimised for OCR

**File types:** TIFF, PDF, PDF/A, JPEG, XPS

**Compression method:** MMR /JPEG

**Features:** Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once

## Fax functions (optional)

**Compatibility:** ITU-T Super G3

**Modem speed:** Max. 33.6 kbps

**Transmission speed:** Less than 3 sec

**Scanning speed:** 2.0 seconds (Quick Scanning, Bitmap)

**Address book:** 200 entries

### Scanning density

Normal: 8 dot/mm x 3.85 line/mm

Fine: 8 dot/mm x 7.7 line/mm

Superfine: 8 dot/mm x 15.4 line/mm

Ultrafine: 16 dot/mm x 15.4 line/mm

Halftone: 256 grey scales

**Maximum original size:** A3, Ledger

**Compression method:** JBIG, MMR, MR, MH

**Memory reception:** 700 sheets or more

**Features:** Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

## Consumables

Average continuous toner yield in accordance with ISO/IEC 19752

**TK-475 Toner Kit:** Microfine toner black for 15,000 pages A4

Capacity of starter toner is 3,000 pages A4

## Options

### Fax System (U)

#### Paper handling

**PF-470 Paper feeder:** Max. 500 sheets; 60–163 g/m<sup>2</sup>; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)

**PF-471 Paper feeder:** Max. 1,000 sheets; 60–163 g/m<sup>2</sup>; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)

**DF-470\* Document finisher + AK-470:** Max. 500 sheets A4, 60–163 g/m<sup>2</sup>; A3, A4, A5, B5, Letter, Legal, Custom (98x148 to 297x432 mm), 3 positions stapling up to 50 sheets A4 or 25 sheets A3

\*Bridge unit AK-470 is required for the use of DF-470

#### Memory upgrade

MDDR2-1024: 1,024 MB

**CF\*-Card:** CF-4 (4 GB) for printing forms, fonts, logos, macro storage and for HyPAS™ applications

**USB Flash Memory:** Supports direct printing and scanning of PDF, XPS, TIFF, JPEG files via USB Host interface

**UG-33:** ThinPrint support

**USB IC Card Reader + Card Authentication Kit (B):** Support for various authentication keys available

#### Optional interface

**IB-50:** Gigabit-Ethernet board 10BaseT/100BaseTX/1000BaseT

**CB-470 Cabinet:** Wooden desk with storage capacity, including castors (wheels)

**CB-471 Base unit:** Wooden base for height increase (to be used only with PF-470 or PF-471)

**CB-472 Cabinet:** Metal desk with storage capacity, including castors (wheels)

**CB-473 Base unit:** Metal base for height increase (to be used only with PF-470 or PF-471)

## Warranty

2-year warranty as standard.\*\* KYOCERA guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

**KYO LIFE** Up to 5-year on-site warranty extensions available for product and options.



Your K Partner:



KYOCERA Document Solutions (UK) Ltd, 8 Beacontree Plaza, Gillette Way, Reading RG2 0BS  
Tel: 0118 931 1500, Fax: 0118 931 1108  
www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

\* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. \*\* Depending on the country.

**KYOCERA**  
Document Solutions

Product depicted includes optional extras.